

MP-1150

› 2" BT Mobile Thermal Printer



Features



- 100 mm high speed printing
- Built-in multi-language codepages includes Chinese, Japanese and Korean characters
- Combo interface for USB and Bluetooth® (4.0)
- EPSON command and other emulation
- 1D / 2D barcode printing supported
- Easy to set and high volume capacity of paper
- OPOS / JPOS driver supported

Specifications

General	Print Method	Thermal line printing	Language	Character Size	Font A: 24 x 24 (16 C/L) Font B: 24 x 12 (32 C/L) Font C: 16 x 16 (24 C/L) Font D: 16 x 8 (48 C/L)		
	Printing Width	48 mm		Barcode	1D	UPCA, UCPE, EAN13, EAN8, CODE39, CODE25 (ITF), CODEBAR, CODE93, CODE128	
	Paper Width	58 mm			2D	PDF417, QR Code, data matrix	
	Printable Dot No.	384 dots		Environment	Operating Temp.	-10°C~50°C	
	Printing Speed	Up to 100 mm/sec			Storage Temp.	-30°C~70°C	
	Resolution	8 dot/mm			Operating Humidity	30%~80% RH (non-condensing)	
	Paper	Sensors		Paper end, cover open	Storage Humidity	5%~90% RH (expect for paper)	
Cutter		Tear bar	Operating Temp.	-10°C~50°C			
Reliability	Type	Receipt thermal paper	Accessories	Standard	Interface cables, paper roll, power adapter, battery pack, driver CD		
	Thickness	0.06 mm~0.09 mm		Options	Options	Carrying bag with shoulder strap, battery charging pad, belt strap	
Performance	Roll Diameter	Max. 38.0 mm	Language		Character Sets	Alphanumeric characters: 95/Extended characters: 128 x 8 page/International characters: 32	
	Interface	USB 2.0 / Bluetooth® (Ver.4.0)		Code Page		CP-437, Katakana character set, CP-850, CP-852, CP-860, CP-863, CP-865, CP-1252	
Receive Buffer	4KB	Compound Character				Traditional Chinese, Simplified Chinese, Japanese, Korean	
Logo Size	256K						
Software	Emulation	ESC/POS CMD compatible		Physical		Dimensions (W x H x D)	142 x 127 x 154 mm
	Driver	Windows 10/x86 / Windows 8/x86 / Windows 7 x86/x64 / Windows XP x86 / OPOS/JPOS				Weight	250 g (w/o battery & paper roll)
Physical	Adapter	12V/2A				Adapter	12V/2A
	Specified Li-on Battery	7.4V, 2900mAh	Specified Li-on Battery		7.4V, 2900mAh		
Language	Certifications	CE, FCC	Language		Character Sets	Alphanumeric characters: 95/Extended characters: 128 x 8 page/International characters: 32	
	Code Page	CP-437, Katakana character set, CP-850, CP-852, CP-860, CP-863, CP-865, CP-1252			Code Page	CP-437, Katakana character set, CP-850, CP-852, CP-860, CP-863, CP-865, CP-1252	
Compound Character	Traditional Chinese, Simplified Chinese, Japanese, Korean		Compound Character		Traditional Chinese, Simplified Chinese, Japanese, Korean		

Applications

- Field Service
- Public Safety
- Deliveries
- Route Accounting
- Retail & Hospitality
- Manufacturing and Warehouse
- Healthcare
- Parking Citations
- Onboard Transportation



*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.